

HEXAGON HEAD BOLTS UNC, UNF GRADE 4.8 (MILD STEEL HEX BOLT-INCH SIZE)

A5

สกรูเกลียวหยาบ (NC), เกลียวละเอียด (NF) เกรด 4.8

	STANDARD	ANSI B18.2.1
	MATERIAL	SWRCH6R (MILD STEEL)
	COATING	BLACK
	CODE	ANC,ANF ,BNC,BNF ,BFL,BSP
	UPDATE	08-02-2012

d (Diameter)	1/2	5/8	3/4	7/8	1"	1.1/8	1.1/4	1.1/2
p (pitch) NC	13	11	10	9	8	7	7	6
p (pitch) NF	20	18	16	14	12	12	12	12
k (Head Thickness)	7.9	9.9	11.9	13.9	15.5	17.5	19.8	23.8
s (Width across flat)	3/4	15/16	1.1/8	1.5/16	1.1/2	1.11/16	1.7/8	2.1/4
b≤6"	31.7	38.1	44.4	50.8	57.1			
b>6"	38.1	44.4	50.8	57.1	63.5			

Length (inch)	Size							
	1/2	5/8	3/4	7/8	1"	1.1/8	1.1/4	1.1/2
1.1/2								
2"		50	50					
2.1/2		50						
3"		25	50					
3.1/2		25	50					
4"		25	50					
4.1/2		25	25					
5"		25	25					
5.1/2		25	25					
6"		25	25					
6.1/2	50	25	25					
7"	50	25	20					
8"	25	25	15					
9"	25	15	15					
10"	25	15	15					
11"	25	15	15					
12"	25	15	15					
12.1/2"	-	-	ใต้เส้นคู่=เกลียวครึ่ง(PARTIAL THREAD)			-	-	-
13"	25	15	15					
14"	25	15	15					
15"	25	15	15					

d (Diameter)	1/2	5/8	3/4	7/8	1"	1.1/8	1.1/4	1.1/2
p (pitch) NC	13	11	10	9	8	7	7	6
p (pitch) NF	20	18	16	14	12	12	12	12
M (Thickness)	11.1	13.9	16.3	19	21.8	24.6	27	32.5
s (width across flat)	3/4	15/16	1.1/8	1.5/16	1.1/2	1.11/16	1.7/8	2.1/4
Size	1/2	5/8	3/4	7/8	1"	1.1/8	1.1/4	1.1/2
หัวน็อต Hex Nut		100	100	100	100	50	50	50
อีแปะดำ Plain Washer	10 kg	10 kg	10 kg	10 kg	10 kg	10 kg	10 kg	10 kg
สปริงดำ Spring Washer	700	350	200	150	100	50	50	30
Size	1.3/4	2"						
หัวน็อต Hex Nut								
อีแปะดำ Plain Washer								
สปริงดำ Spring Washer								

